What is claimed is:

1. A Media Gateway proxy logically positioned between a Media Gateway Controller

(MGC) and a plurality of Media Gateways comprising:

a frontend for receiving a message from said MGC and parsing said message, said

message containing an attribute, sub-command, and a destination address;

a memory, coupled to said frontend, for storing said message and said attributes,

each of said attributes corresponding to a selected one of said plurality of Media Gateways, each

of said gateways having an address;

middleware, coupled to said frontend, for finding in said memory said address of a

said selected Media Gateway using said destination address and said attribute; and

an internal MGC, coupled to said middleware, for receiving the address of said

gateway, said subcommand, and said attribute, and forming a plurality of other messages using

said sub-command, said address, and said attribute.

15

20

5

10

The Media Gateway proxy of claim 1:

wherein said internal MGC receives replies from said plurality of MGs, each of said

replies containing the transaction completion associated with a selected sub-command; and

wherein said middleware determines if said replies include all of said transaction

completions and wherein said frontend transmits a message when all replies have been received.

-22-

The Media Gateway proxy of claim 2 wherein said messages include transactions

conforming to a media gateway protocol

The Media Gateway proxy of claim 3 wherein said protocol is MEGACO.

5

10

The Media Gateway proxy of claim 1 wherein said plurality of Media Gateways

comprise a virtual grouping.

6. The Media Gateway proxy of claim 5 wherein said destination address is associated

with said virtual grouping.

7. A method of transmitting and processing messages, comprising the steps of:

receiving a message and parsing said message, said message including an attribute,

sub-command, and a destination address;

15

20

storing in memory said message and said attributes, each of said attributes

corresponding to a selected one of said plurality of Media Gateways, each of said gateways

having an address;

finding in said memory said address of a selected one of said Media Gateways using

said destination address and said attribute; and

receiving the address of said gateway, said subcommand, and said attribute and

forming a unique message for each of said sub-commands, said addresses, and said attributes.

-23-

8. The method of claim 7 comprising the further steps of:

receiving replies from said plurality of MGs, each of said replies including the

transaction completion of selected one of said sub-commands;

determining if said replies include all of said transaction completions; and

transmitting a message when all replies have been received.

9. The method of claim 8 wherein said messages conform to a Media Gateway

protocol.

5

10

15

20

10. The method of claim 9 wherein said protocol is MEGACO.

11. The method of claim 8 wherein said destination address is the address of a virtual

Media Gateway.

12. A method of transmitting reply messages from Media Gateways to a Media Gateway

Controller, wherein each of said reply messages received is in response to a message containing

a sub-command, and all of said sub-commands contained in a single message, said method

comprising the steps of:

receiving a reply message from a Media Gateway; and

determining whether all replies have been received in response to said messages.

-24-

13. A computer readable medium having stored therein instructions for causing a processing unit to execute the following method:

receiving a message and parsing said message, said message including an attribute, sub-command, and a destination address;

storing said message and said attributes, each of said attributes corresponding to a selected one of said plurality of Media Gateways, each of said gateways having an address;

finding in said memory said address of a selected one of said Media Gateways using said destination address and said attribute; and

receiving the address of said gateway, said subcommand, and said attribute and forming a unique message for each of said sub-commands, said addresses, and said attributes.

14. A device for transmitting and processing messages comprising:

a first receiver that receives a message and parses said message, said message containing an attribute, sub-command, and a destination address;

a memory, coupled to said first receiver, that stores said message and said attributes, each of said attributes corresponding to a selected one of said plurality of Media Gateways, each of said gateways having an address;

a locator, coupled to said memory, that finds in said memory said address of a said selected Media Gateway using said destination address and said attribute; and

a second receiver, coupled to said locator, that receives the address of said gateway, said subcommand, and said attribute and forms messages using said sub-command, said address, and said attribute.

5

10

15

20

15. The device of claim 14 further comprising:

a third receiver for receiving replies from said plurality of MGs, each reply

containing transaction completions for a sub-command;

a determiner for determining if all of said sub-commands have been received; and

a transmitter for transmitting a message when all transaction completions of said

sub-commands have been received.

5

10

15

20

16. A network comprising:

a Media Gateway Controller (MGC);

a Media Gateway proxy, said proxy coupled to said MGC and comprising:

a first receiver that receives a message and parses said message, said message

containing an attribute, sub-command, and a destination address;

a memory, coupled to said first receiver, that stores said message and said attributes,

each of said attributes corresponding to a selected one of said plurality of Media Gateways, each

of said gateways having an address;

a locator, coupled to said memory, that finds in said memory said address of a said

selected Media Gateway using said destination address and said attribute; and

a second receiver, coupled to said locator, that receives the address of said gateway,

said subcommand, and said attribute and forms messages using said sub-command, said address,

and said attribute; and

a plurality of Media Gateways coupled to said Media Gateway proxy.

-26-